

Supplier: SunEarth, Inc. 8425 Almeria Avenue Fontana, CA 92335 USA www.sunearthinc.com Reference Standard:

SRCC Standard 100-2008-02

Brand: Empire

Model: EP-40 / EP-40-0.75

Collector Type: Glazed Flat Plate

Certification #: 2007032A
Original Certification: June 25, 2009
Renewal Expiration Date: October 01, 2022


Certifications must be renewed annually.

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation™ (ICC-SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

| COLLECTOR THERMAL PERFORMANCE RATINGS |                                 |                           |                        |                          |                           |                                  |                    |  |  |
|---------------------------------------|---------------------------------|---------------------------|------------------------|--------------------------|---------------------------|----------------------------------|--------------------|--|--|
|                                       | Kilowatt-hours (th              | ermal) Per Panel Per [    | Day                    |                          | Thousands of              | Btu Per Panel Per Day            | ,                  |  |  |
| Climate ->                            | High Radiation                  | Medium Radiation          | Low Radiation          | Climate ->               | High Radiation            | Medium Radiation                 | Low Radiation      |  |  |
| Category<br>(Ti-Ta)                   | (6.3 kWh/m².day)                | (4.7 kWh/m².day)          | (3.1 kWh/m².day)       | Category<br>(Ti-Ta)      | (2000 Btu/ft².day)        | (1500 Btu/ft².day)               | (1000 Btu/ft².day) |  |  |
| A (-5 °C)                             | 15.5                            | 11.6                      | 7.8                    | A (-9 °F)                | 53.0                      | 39.7                             | 26.6               |  |  |
| B (5 °C)                              | 14.6                            | 10.7                      | 6.8                    | B (9 °F)                 | 49.7                      | 36.5                             | 23.3               |  |  |
| C (20 °C)                             | 12.5                            | 8.7                       | 4.9                    | C (36 °F)                | 42.6                      | 29.7                             | 16.8               |  |  |
| D (50 °C)                             | 7.3                             | 3.8                       | 0.8                    | D (90 °F)                | 24.8                      | 13.0                             | 2.8                |  |  |
| E (80 °C)                             | 1.8                             | 0.0                       | 0.0                    | E (144 °F)               | 6.1                       | 0.0                              | 0.0                |  |  |
| A- Pool Heati                         | ng (Warm Climate) <b>B</b> - Po | ol Heating (Cool Climate) | C- Water Heating (Warm | Climate) <b>D</b> - Spac | e & Water Heating (Cool ( | Climate) <b>E</b> - Commercial H | ot Water & Cooling |  |  |

| TECHNICAL RES  | ULTS                               |                      |              | Tested in accordance with: ISO 9806:1994 |        |           |              |         |
|--|------------------------------------|----------------------|--------------|--|--------|-----------|--------------|---------|
| ISO Efficiency Equ   | ation [NOTE: Based                 | on gross area and (I | P)=Ti-Ta]    |  |        |           |              |         |
| SI UNITS: η= 0.718 - 2.29060(P/G) - 0.04398(P²/G) Y Intercept: 0.744 Slope: -5.151 W/m².°C |                                    |                      |              |  |        |           |              | //m².°C |
| IP UNITS:  | η= 0.718 -                         | 0.40370(P/G) - 0.00  | Y Intercept: | 0.744                                    | Slope: | -0.908 Bt | tu/hr.ft².°F |         |
| Incident Angle Mo  | difier                             |                      |              |  |        |           | -            |         |
| θ  | 10°                                | 20°                  | 30°          | 40°                                      | 50°    | 6         | 000          | 70°     |
| Κτα  | 1.00 0.98 0.96 0.91 0.84 0.71 0.44 |                      |              |  |        |           |              |         |
|  | •                                  |                      | Impact S     | Safety Rating:                           | •      | -         |              |         |

| COLLECTOR SPECIFICATIONS |          |           |                 |           |          |  |  |
|--------------------------|----------|-----------|-----------------|-----------|----------|--|--|
| Gross Area:              | 3.800 m² | 40.90 ft² | Dry Weight:     | 64.4 kg   | 142.0 lb |  |  |
| Net Aperture Area:       | 3.449 m² | 37.12 ft² | Fluid Capacity: | 4.8 liter | 1.3 gal  |  |  |
| REMARKS:                 |          |           |                 |           |          |  |  |







Supplier: SunEarth, Inc. 8425 Almeria Avenue Fontana, CA 92335 USA www.sunearthinc.com

Reference Standard:

SRCC Standard 100-2008-02

Brand: Empire

Model: EP-40 / EP-40-0.75

Certification #: 2007032A

Original Certification: June 25, 2009

Renewal Expiration

Collector Type:

October 01, 2022

Glazed Flat Plate

Date:

Certifications must be renewed annually.

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation™ (ICC-SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

| ADDITIONAL INFORMATION (click here to return to the rating page) |                                   |                                      |                |          |         |  |  |  |
|--|-----------------------------------|--------------------------------------|----------------|----------|---------|--|--|--|
| COLLECTOR TESTING  | COLLECTOR TESTING INFORMATION     |                                      |                |          |         |  |  |  |
| Test Lab:  | Bodycote                          | Bodycote Test Date: January 05, 2009 |                |          |         |  |  |  |
| Test Report Number:  | 07-08-0532 Test Location: indoors |                                      |                |          |         |  |  |  |
| Test Fluid:  | Water                             |                                      |                |          |         |  |  |  |
| Test Mass Flow Rate:   | 0.0200 kg/(s m²)                  | 14.75 lb/(hr ft²)                    | Test Pressure: | 1103 kPa | 160 psi |  |  |  |

| SOLAR COLLECTOR | CONSTRUCTION DETA | AILS         |         |              |          |
|-----------------|-------------------|--------------|---------|--------------|----------|
| Gross Length:   | 0.000 m           | Gross Width: | 0.000 m | Gross Depth: | 0.000 mm |

| COLLECTOR MATERIALS   |                   |        |                 |                        |             |        |            |  |
|-----------------------|-------------------|--------|-----------------|------------------------|-------------|--------|------------|--|
| Outer Cover:          | Ot                | her    | Enclosure back: | Aluminum               | Back Insula | ation: | , Foam     |  |
| Inner Cover:          | Inner Cover: None |        | Enclosure side: | Aluminum               | Side Insula | ition: | Foam, None |  |
| Absorber Description: |                   |        |                 | Flow Pattern:          |             |        |            |  |
| Riser Tube:           |                   | Copper | Fin:            |                        |             |        |            |  |
| Absorber Coating:     |                   | 1      | Non-selective   | Tube to fin connection |             |        |            |  |

| GLAZING                                | Outer Cover | Inner Cover |
|--|-------------|-------------|
| Material:                              | Other       | None        |
| Surface Characteristics:               |             |             |
| Thickness:                             | 0.0 mm      | N/A         |
| Transmissivity:                        |             |             |
| Length:                                | 0.000 m     |             |
| Width:                                 | 0.000 m     |             |
| Tube Glazing to Header Enclosure Seal: |             |             |

|--|





Supplier: SunEarth, Inc. 8425 Almeria Avenue Fontana, CA 92335 USA www.sunearthinc.com

Reference Standard: SRCC Standard 100-2008-02

Brand: Empire

Model: EP-40 / EP-40-0.75

Collector Type: Glazed Flat Plate

Original Certification: June 25, 2009

Renewal Expiration

Certification #:

October 01, 2022

2007032A

Date:

Certifications must be renewed annually.

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation™ (ICC-SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

| Header Material:                                |               |     | Header OD:         |                             | Header Wall:                                     |           |
|---|---------------|-----|--------------------|-----------------------------|--|-----------|
| Riser Tube Material:                            |               |     | Riser Tube OD:     |                             | Riser Tube Wall<br>Thickness:                    |           |
| Fin Material:                                   |               |     | Fin Thickness:     | 0.00 mm                     |  |           |
|   | _             |     |                    |                             |  |           |
| Flow Pattern:                                   |               |     |                    |                             |  |           |
| Number of Riser<br>Tubes:                       | 0             |     | Tube Spacing:      |                             | Number of times each riser crosses the absorber: | 0         |
| <b>Length of Flow Path:</b> 0.00 m              |               |     | Riser to Fin/Plate |                             |  |           |
|   |               |     | Bond:              |                             |  |           |
| INCLUATION:                                     |               |     | Bond:              |                             |  |           |
| INSULATION: Location                            | Ту            | /pe | Bond: Thickness    | Location                    | Type   | Thickness |
|   | Ту            | ре  |                    | Location Sides – Inner Laye | Type : Foam                                      | Thickness |
| Location  | Ty            | /ре |                    |                             | : Foam   | Thickness |
| Location<br>Back – Top Layer:                   | Foam          | уре |                    | Sides - Inner Laye          | : Foam   | Thickness |
| Location Back – Top Layer: Back – Bottom Layer: | Foam          | rpe |                    | Sides - Inner Laye          | : Foam   | Thickness |
| Location Back – Top Layer: Back – Bottom Layer: | Foam lethods: | rpe |                    | Sides - Inner Laye          | : Foam   | Thickness |

| PRESSURE DROP |    |      |        |  |  |  |  |  |
|---------------|----|------|--------|--|--|--|--|--|
| Flow          | ΔΡ | Flow | ΔΡ     |  |  |  |  |  |
| ml/s          | Pa | gpm  | in H₂0 |  |  |  |  |  |
| 20            |    | 0.32 |        |  |  |  |  |  |
| 50            |    | 0.79 |        |  |  |  |  |  |
| 80            |    | 1.27 |        |  |  |  |  |  |





Supplier: SunEarth, Inc. 8425 Almeria Avenue Fontana, CA 92335 USA www.sunearthinc.com Reference Standard:

SRCC Standard 100-2008-02

Brand: Empire

Model: EP-40 / EP-40-0.75
Collector Type: Glazed Flat Plate

Certification #: 2007032A

Original Certification: June 25, 2009

Renewal Expiration October 01, 2022

Date:

Certifications must be renewed annually.

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation™ (ICC-SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

#### ICC-SRCC OG-100 Certification Label

The collectors listed in this certification must display the label below.

The certification label must be permanently affixed to each collector in accordance with SRCC OG-100 program requirements.



