


Certifications must be renewed annually.

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation™ (ICC-SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

	COLLECTOR THERMAL PERFORMANCE RATINGS										
	Kilowatt-hours (the	ermal) Per Panel Per [Day		Thousands of	Btu Per Panel Per Day	,				
Climate ->	High Radiation	Medium Radiation	Low Radiation	Climate ->	High Radiation	Medium Radiation	Low Radiation				
Category (Ti-Ta)	(6.3 kWh/m².day)	(4.7 kWh/m².day)	(3.1 kWh/m².day)	Category (Ti-Ta)	(2000 Btu/ft².day)	(1500 Btu/ft².day)	(1000 Btu/ft².day)				
A (-5 °C)	15.5	11.6	7.8	A (-9 °F)	53.0	39.7	26.6				
B (5 °C)	14.6	10.7	6.8	B (9 °F)	49.7	36.5	23.3				
C (20 °C)	12.5	8.7	4.9	C (36 °F)	42.6	29.7	16.8				
D (50 °C)	7.3	3.8	0.8	D (90 °F)	24.8	13.0	2.8				
E (80 °C)	1.8	0.0	0.0	E (144 °F)	6.1	0.0	0.0				
A- Pool Heati	ng (Warm Climate) B - Poo	ol Heating (Cool Climate)	C- Water Heating (Warm	Climate) D - Spac	e & Water Heating (Cool (Climate) E - Commercial H	ot Water & Cooling				

TECHNICAL RES	ULTS			Tested in accorda	Tested in accordance with: ISO 9806:1994						
ISO Efficiency Equ	ISO Efficiency Equation [NOTE: Based on gross area and (P)=Ti-Ta]										
SI UNITS: n= 0.718 - 2.29060(P/G) - 0.04398(P ² /G) Y Intercept:					0.744	Slope:	-5.151 W	//m².°C			
IP UNITS:	η= 0.718 - 0.40370(P/G) - 0.00430(P²/G)			Y Intercept:	0.744	Slope:	-0.908 B	tu/hr.ft².°F			
Incident Angle Mo	difier										
θ 10 ⁰ 20 ⁰ 30 ⁰ 40 ⁰ 50 ⁰ 60 ⁰ 70							70 ⁰				
Κτα	1.00	0.91	0.84	0.	71	0.44					
	Impact Safety Rating:										

COLLECTOR SPECIFICATIONS								
Gross Area:	3.800 m ²	40.90 ft ²	Dry Weight:	68.2 kg	150.4 lb			
Net Aperture Area:	3.449 m ²	37.12 ft ²	Fluid Capacity:	6.1 liter	1.6 gal			
REMARKS:	REMARKS:							



Shawn Martin

CORPORATION'

Technical Director

Print Date: January 20, 2022 Page 1 of 4 Please verify certification is active on the SRCC website www.solar-rating.org. © Solar Rating & Certification Corporation™ (ICC-SRCC) 3060 Saturn Street, Suite 100, Brea, CA 92821

	OG-100 ICC-SRCC™	CERTIFIED SOLAR COLLECTOR	# 2007032F
	Supplier:	Brand:	Empire
	SunEarth, Inc. 8425 Almeria Avenue	Model:	EP-40-1.5
(ICC-SRCC)	Fontana, CA 92335 USA	Collector Type:	Glazed Flat Plate
	www.sunearthinc.com	Certification #:	2007032F
SOLAR RATING	Reference Standard:	Original Certification:	June 25, 2009
& CERTIFICATION CORPORATION	SRCC Standard 100-2008-02	Renewal Expiration Date:	October 01, 2022
		Certifications must be re	enewed annually

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation[™] (ICC-SRCC[™]), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

	ADDITIONAL INFORMATION (click here to return to the rating page)										
COLLECTOR TESTING	COLLECTOR TESTING INFORMATION										
Test Lab:	Bodycote	Bodycote Test Date: January 05, 2009									
Test Report Number:	07-08-0532		Test Location:								
Test Fluid:	Water										
Test Mass Flow Rate:	ass Flow Rate: 0.0200 kg/(s m²) 14.75 lb/(hr ft²) Test Pressure: 1103 kPa 160 psi										

SOLAR COLLECTOR	CONSTRUCTION DETA	ILS			
Gross Length:	0.000 m	Gross Width:	0.000 m	Gross Depth:	0.000 mm

COLLECTOR MATERIALS

	-						
Outer Cover: Oth		her Enclosure back:		Aluminum Back Insula		ation:	, Foam
Inner Cover: None		one	Enclosure side:	Aluminum	Side Insula	tion:	Foam, None
Absorber Description:				Flow Pattern:			
Riser Tube:			Copper	Fin:			
Absorber Coating:		Мос	derately selective	Tube to fin connection			

GLAZING	Outer Cover	Inner Cover
Material:	Other	None
Surface Characteristics:		
Thickness:	0.0 mm	N/A
Transmissivity:		
Length:	0.000 m	
Width:	0.000 m	
Tube Glazing to Header Enclosure Seal:		

ABSORBER:

Absorber Coating:

Moderately selective



Print Date: January 20, 2022 Page 2 of 4 Please verify certification is active on the SRCC website www.solar-rating.org. © Solar Rating & Certification Corporation™ (ICC-SRCC) 3060 Saturn Street, Suite 100, Brea, CA 92821

	OG-100 ICC-SRCC™	CERTIFIED SOLAR COLLECTOR	# 2007032F
	Supplier:	Brand:	Empire
	SunEarth, Inc. 8425 Almeria Avenue	Model:	EP-40-1.5
(ICC-SRCC)	Fontana, CA 92335 USA	Collector Type:	Glazed Flat Plate
	www.sunearthinc.com	Certification #:	2007032F
SOLAR RATING	Reference Standard:	Original Certification:	June 25, 2009
& CERTIFICATION CORPORATION	SRCC Standard 100-2008-02	Renewal Expiration Date:	October 01, 2022
		Certifications must be re	enewed annually.

This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation[™] (ICC-SRCC[™]), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

Header Material:		Header OD:		Header Wall:	
Riser Tube Material:	Copper	Riser Tube OD:		Riser Tube Wall Thickness:	
Fin Material:		Fin Thickness:	0.00 mm		

Flow Pattern:				
Number of Riser Tubes:	0	Tube Spacing:	Number of times each riser crosses the absorber:	0
Length of Flow Path:	0.00 m	Riser to Fin/Plate Bond:		

INSULATION:									
Location	Туре	Thickness	Location	Туре	Thickness				
Back – Top Layer:			Sides – Inner Layer:	Foam					
Back – Bottom Layer:	Foam		Sides – Outer Layer:	None					
Enclosure Fastening M	lethods:								

Power Output per Collector(W) [Ti-Ta, G = 1000 W/m ²]							
0	10	30	50	70			

PRESSURE DROP

Flow	ΔΡ		Flow	ΔΡ		
ml/s	Pa		gpm	in H₂0		
20			0.32			
50			0.79			
80			1.27			



Print Date: January 20, 2022 Page 3 of 4 Please verify certification is active on the SRCC website www.solar-rating.org. © Solar Rating & Certification Corporation™ (ICC-SRCC) 3060 Saturn Street, Suite 100, Brea, CA 92821



This solar collector has been evaluated and certified by the Solar Rating & Certification Corporation[™] (ICC-SRCC[™]), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with the SRCC OG-100 Certification Program, as defined in SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors. This award of certification is subject to all terms and conditions of the current OG-100 Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

ICC-SRCC OG-100 Certification Label

The collectors listed in this certification must display the label below.

The certification label must be permanently affixed to each collector in accordance with SRCC OG-100 program requirements.





Print Date: January 20, 2022 Page 4 of 4 Please verify certification is active on the SRCC website www.solar-rating.org. © Solar Rating & Certification Corporation™ (ICC-SRCC) 3060 Saturn Street, Suite 100, Brea, CA 92821